Large Format Media Product Information Document



Satin Photo Paper - 200 g/m² - 6061B

1	Product	Grammage / (g/m²)	Thickness (μ)	Width / mm	Length / m	Mercury Code (EAN128)	Article number	Canon iPF5100	Canon iPF6100	Canon iPF6200	Canon iPF6300	Canon iPF6350	Canon iPF6000S	non iPF63	ldi uo	on iPF	Canon iPF8000S	in in a	anon ibFano	non iPF510	Canon iPF610	Canon iPF605	Canon iPF650	Canon iPF655	Canon iPF710	iΡF	anon iPF75	on iPF75	5				c 1	Canon LP24
	atin	200	205	432	30	6061B001AA	97003174	v	v	v	v	v	v	v	v	v	v١	/ \	/ v	v	v	v	v	v	٧	v	v	v	v	v	v١	, I	v١	v
	Photo	200	205	610	30	6061B002AA	97003175		v	v	v	v	v	v	v	v	v١	/ \	/ v	,	v	v	v	v	v	v	v	v	v	v	v١	,	,	v
P	aper	200	205	914	30	6061B003AA	97003176								v	v	v١	/ \	/ v	,					v	v	v	v	v	v	v١	,		
		200	205	1067	30	6061B004AA	97003177								v	v	v١	/ \	/ v										v	v	٧V	,		
		200	205	1524	30	6061B005AA	97003178											١,	/ v	,														



Description: This top quality photo inkjet paper has a quality photo coating for high grade natural

colour prints of graphic pictures, presentations and photos. The paper is instant dry, is smudge resistant and provides good colour density and excellent image sharpness. This paper is compatible with a large range of dye and pigment digital printing systems, and is the most ideal product for users who need top quality photographic

re-productions.

Features: Extremely quick drying, dye and pigment ink compatible, good colour density,

excellent image sharpness, smudge resistant, lamination not necessary, easy handling.

Applications: Photography, portraits, posters, graphic art reproductions, exhibition graphics,

indoor and outdoor signage.

Physical Properties:

Weight Caliper	200 g/m² 205 µm	±7 ±5
Curl at 23 °C, 50% RH	0 mm	±8
Gloss (Tappi) 75° Opacity	52 95.0%	±5
Colour (CIE Lab) D50 /2°	L* 95.5	±0.5
Colour (CIL Lab) D30 /2	a* 1.03	±0.5
	b* -7.05	±0.8

Printing: For optimum results select the best possible print settings.

Advised Driver / panel settings: Satin Photo Paper 200gsm / SatinPhoto 200g

Finishing: To add surface protection from dirt, abrasion and gas-fading, lamination is recommended. Although ink drying is virtually immediate, it is still

recommended to allow a waiting time of approximately 3 hours before lamination. In order to prevent moisture ingress and paper splitting, lamination with a 5-6 mm encapsulated edge is also recommended. Laminate must be evenly applied to the

print in order to avoid curling. Both hot and cold lamination is possible.

Ideal Storage Conditions:

Store paper only in original boxes, out of direct sunlight and under normal climatic conditions (23 °C, 50% RH) until ready to use. Allow material to adapt to room conditions before use. Papers can absorb moisture in humid conditions or lose moisture in low humidity conditions. Highly humid conditions make the ink drying time longer and this could interfere with proper laminate adhesion.

Shelf Life:

2 years from shipping date when stored under ideal conditions (see above)

'A Whole Wide World of Media Excellence'