HP PageWide XL 3900 Multifunction Printer



Do the work of two printers with one – faster and lower cost than LED¹



Fast – immediate, simple access to final prints

- Don't waste time waiting for prints with speeds up to 6 D/A1 pages/min and a fast 30-second first page out.
- Gain reassurance that the print will turn out as you expect with one-click printing from HP Click.²
- Anyone can copy and scan with intuitive multifunction workflows, including automatic background removal.
- Focus on your project, not the printer with up to 4 rolls and integrated 100-page top stacker.

Save – help keep costs under control

- Run at lower costs than low-volume LED¹ in monochrome and colour.
- Gain broad control over your printing costs and turn them to your advantage with HP SmartTracker software.
- Use half the energy per page compared to equivalent LED printers.³
- Secure data and help cut breach-related costs self-encrypted HDD, Secure Disk Erase, and role access control.

Consolidate – mono and colour printing in one

- Improve manageability and simplify your workflow with one device for mono and colour.
- Help meet all your needs, from job preparation to finishing, with a fully integrated HP solution.
- Produce excellent technical prints vivid colour, crisp lines, fine detail, smooth grayscales that beat LED.⁴
- Work with durable moisture/fade-resistant prints, even on uncoated bond, with HP PageWide XL pigment inks.⁵

For more information, please visit http://www.hp.com/go/pagewidexl3900

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Printing up to 6 D/A1 pages/minute, the HP PageWide XL 3900 Multifunction Printer is faster than alternative low-volume LED printers and MFPs (under 6 D/A1 pages/minute) as of November, 2018. Operational costs for printers based on low-volume LED technology under €20,000 in the market as of January, 2019. Operational costs consist of supplies and service costs. For testing criteria, see http://www.hp.com/go/pagewidexlclaims.

2 Once image is selected, one-click printing when printing the entire file without any modifications to the print settings. Applicable to PDF, JPEG, TIFF, and HP-GL/2 files.

³ Conclusions based on internal HP testing for a specific use scenario. Comparable printers using LED technology based on LED printers capable of printing 4-6 DJA1 pages per minute and which represent more than 80% of the share of mid-volume LED printers in the US and Europe according to IDC as of November, 2018. For testing criteria, see http://www.hp.com/go/pagewidexlclaims.

⁴ For output produced with HP PageWide XL printers and LED printers from different manufacturers and that represent greater than 50% of the annual shipments of LED printers in North America as of 2018 according to

⁴ For output produced with HP PageWide XL printers and LED printers from different manufacturers and that represent greater than 50% of the annual shipments of LED printers in North America as of 2018 according to IDC. For testing criteria, see http://www.hp.com/go/pagewidexlclaims.

⁵ Compared to prints produced with HP 970/971/980 inks that are fade and moisture resistant per ISO 11798 Permanence and Durability Methods certification. For testing criteria, see

⁵ Compared to prints produced with HP 970/971/980 inks that are fade and moisture resistant per ISO 11798 Permanence and Durability Methods certification. For testing criteria, see http://www.hp.com/go/pagewidexlclaims.

Technical specifications

| Ca | nor | 1 | |
|----|-----|---|--|

| General | |
|---------------------------------------|---|
| Descriptions | Large-format colour MFP |
| Technology | HP PageWide Technology |
| Applications | Line drawings; Maps; Orthophotos; Posters |
| Ink types | Pigment-based (cyan, magenta, yellow, black) |
| Ink cartridges | 4 (1 x 400 ml per colour) |
| Printheads | 8 x HP 841 PageWide XL Printheads |
| Average printhead life | 32 liters |
| Printhead warranty | 10 liters or 12 months from installation |
| Print resolution | 1200 x 1200 dpi |
| Minimum line width | 0.02 mm (HP-GL/2 addressable) (0.0008 in (HP-GL/2 addressable)) |
| Guaranteed minimum line width | 0.085 mm (ISO/IEC 13660:2001(E)) (0.0033 in (ISO/IEC 13660:2001(E))) ¹ |
| Line accuracy | ±0.1% ² |
| Print speed | |
| A1/Arch D/ANSI D (long edge first) | 6 pages/min |
| Warm-up time | No warm up |
| First page out | 30 sec (from Ready mode) |
| Media | |
| Media rolls | 2 rolls default with auto-switching, expandable to 4 rolls |
| Roll width | 279 to 1016 mm (11 to 40 in) |
| Roll length | Up to 200 m (Up to 650 ft) |
| Roll diameter | Up to 177 mm (Up to 7 in) |
| Roll core diameter | 7.6 cm (3 in) |
| Media weight | 70 to 200 g/m² (19 to 53 lb) |
| Media thickness | Up to 15.7 mil Up to 0.4 mm |
| Media types | Bond and recycled papers, poster papers, polypropylene, tyvek papers, matte film |
| Media output | Standard: Top stacker Optional: High Capacity Stacker, online folder (only compatible in conjunction with the optional accessory upgrade kit) |
| Scanner | |
| Description | 91 cm (36 in) CIS scanner |
| Speed | Colour: up to 7.62 cm/sec (up to 3 in/sec); Greyscale: up to 25.4 cm/sec (up to 10 in/sec) |
| Optical resolution | 1200 dpi |
| Scan width | Up to 914 mm (up to 36 in) |
| Original thickness | Up to 0.26 mm (up to 0.01 in) |
| Maximum copy length | 9.5 m (374.5 in) |
| Maximum scan length | 18 m (708.7 in) (TIFF, 610 mm (24 in) wide original at 200 dpi), 8 m (315 in) (JPEG), 5 m (196.9 in) (PDF) |
| Scan format | Standard: JPEG, TIFF; Optional: PDF 1.4, multi-page PDF 1.4 (with PS/PDF upgrade) |
| Scan features | Preview with cropping, scan quicksets, batch scanning |
| Scan destination | USB, network folder (SMB), scan to email, scan to HP SmartStream software, scan to FTP |
| Embedded controller | |
| Processor | Intel Core i3 |
| Memory | 8 GB DDR3 |
| Hard drive | 1 x 500 GB HDD, self-encrypted with AES-256 |
| Print languages | Standard: HP-GL/2, TIFF, JPEG Optional: Adobe PostScript 3, Adobe PDF 1.7 (with PS/PDF upgrade) |
| Remote management | HP Partner Link, HP Embedded Web Server, HP Web Jetadmin |
| Connectivity | |
| Interfaces | TCP/IP, BootP/DHCP, USB 2.0 host (certified) |
| Printing paths | HP SmartStream software (optional), HP Click printing software, HP Universal Print Driver |
| | (HP-GL/2 and PS), HP PageWide XL print drivers (PDF, HP-GL/2, and PS) |
| User interface | |
| User interface | 203 mm (8 in) capacitive touchscreen |
| Dimensions (w x d x h) | |
| Printer | 1960 x 864 x 1303 mm (77.2 x 34 x 51.3 in) ³ |
| Shipping | 2180 x 1068 x 1764 mm (86.8 x 42.1 x 69.5 in) |
| Weight | |
| Printer | 430 kg (948 lb) |
| Shipping | 546 kg (1204 lb) |
| - 663 | 3 |

Environmental

| Operating temperature | 5 to 40°C (41 to 104°F) | |
|-----------------------|---|--|
| Operating humidity | 20 to 80% RH, depending on media type | |
| Acoustics | | |
| Sound pressure | Printing: ≤ 55 dB(A); Ready: ≤ 35 dB(A); Sleep: ≤ 16 dB(A) | |
| Sound power | Printing: ≤ 7.3 B(A); Ready: ≤ 5.2 B(A); Sleep: ≤ 4.2 B(A) | |
| Power | | |
| Consumption | 0.4 kW (typical); 0.7 kW (max printing); 108.4 W (ready); < 1 W (< 4.6 W with embedded Digital Front End) (sleep) | |
| Requirements | Input voltage (auto ranging) 100-127/200-240 V (±10%), 50/60 Hz (±3 Hz), 7/3.5 A | |
| Certification | | |
| Safety | IEC 60950-1+A1+A2 compliant; EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC) | |
| Electromagnetic | Compliant with Class A requirements, including: EU (EMC Directive) | |
| Environmental | ENERGY STAR, EPEAT Silver, CE marking (including RoHS, WEEE, REACH). In compliance with WW RoHS materials restriction requirements in Turkey, Serbia, and Ukraine | |
| Warranty | 90 days | |

Ordering information

Product 6CC85A

| Accessories | |
|-------------|--|
| 1AT07B | HP PageWide XL 3900/4x00 Accessory Upgrade Kit |
| CZ317A | HP PageWide XL PostScript/PDF Upgrade Kit |
| CZ318A | HP PageWide XL Drawer |
| 3JJ54A | HP F40 Folder |
| L3J69AAE | HP SmartStream Preflight Manager |
| 2NH46AAE | HP SmartStream Document Organizer Module |
| 2NH47AAE | HP SmartStream Pixel Analysis Module |
| L3J76AAE | HP SmartStream Print Controller for HP PageWide XL 4x00 Printer series |
| ECC8EVVE | HD SmartTracker for HD VI 3000 Printer corine |

HP PageWide XL 3900 40-in Multifunction Printer with Top Stacker

Original HP ink cartridges and maintenance supplies

| 1XB40A | HP 849 400-ml Black PageWide XL Ink Cartridge |
|--------|---|
| 1XB37A | HP 849 400-ml Magenta PageWide XL Ink Cartridge |
| 1XB38A | HP 849 400-ml Yellow PageWide XL Ink Cartridge |
| 1XB39A | HP 849 400-ml Cvan PageWide XI. Ink Cartridge |

ECO highlights

- Save paper with automatic print settings and image nesting
 ENERGY STAR® certified¹ and EPEAT® Silver registered²
 Free, convenient HP ink cartridge recycling³
 FSC®-certified papers⁴, recyclable HP media; some HP media eligible for take-back program⁵

¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental

1 ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.
2 EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
3 Program availability varies. Please check http://www.hp.com/recycle for details.
4 BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. HP LFM Redia.com. For information about HP large format printing materials, please visit http://www.HPLFMedia.com.
5 Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.

Please recycle large-format printing hardware and printing supplies. Find out how at our website: $\label{eq:hydro} \text{http://www.hp.com/ecosolutions}$

1 Measured on HP Universal Bond paper.
2 ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Polypropylene and HP PageWide XL pigment ink.
3 Depth: 800 + 64 mm (31.5 + 2.5 in) removable scanner input tray to pass through doorways.























