

XPLPRO200

Xativa X-Press Lustre Pro Photo Paper



An exceptional 200gsm lustre finish photo paper with a special high quality ink receiver layer and micro-porous coating provides instant dry printing with brilliant colour depth.

Ideal for posters, indoor displays, presentations to photo enlargements and fine art reproductions.

Produce vivid colour with excellent image sharpness using Xativa X-Press Lustre Pro Photo Paper. Its special high quality ink receiver layer and double sided polyethylene coating provides prints that are instantly dry and smudge resistant straight from the printer.

This paper is also universally compatible with all common dye, pigmented and latex inks.

All specifications are correct at time of print and are subject to change without notice. E&OE

Product specifications

Weight	200 g/m ² (+/- 10gsm) DIN EN ISO536	
Thickness	207 microns (+/- 12 microns) ISO534	
Opacity	> 94% (+/- 3%) DIN53146	
Whiteness	136 (+/- 6%) ISO11475	
Finish	Lustre	
Shade	L	96.0 (+/- 2)
	a	1.5 (+/- 1)
	b	-10.5 (+/- 2)
Smoothness	> 250 ISO5627	
Gloss value 60°	20 (+/- 4)	
Operating temperature	15 to 100 degrees centigrade	
Operating humidity	20 to 80% RH	
Dry time	Instant dry with heating (at 23 degrees centigrade, 50% RH)	
Shelf time	2 years, unopened in original packaging	
Storage temperature	0 to 40 degrees centigrade	
Storage humidity	5 to 95% RH	
Country of origin	Product of Germany	
Printer / Ink Compatibility	Compatible with all aqueous based dye, pigment, latex and UltraChrome K3 Inks from all leading manufacturers such as Canon, Epson and Hewlett Packard	
Lamination	Can be laminated with commercially available thermal and pressure sensitive films	
Ordering information	Product numbers	Roll Sizes
	XPLPRO200-17	432mm x 30m
	XPLPRO200-24	610mm x 30m
	XPLPRO200-36	914mm x 30m
	XPLPRO200-42	1067mm x 30m
	XPLPRO200-42-60	1067mm x 60m
	XPLPRO200-60	1524mm x 30m
	XPLPRO200-60-60	1524mm x 60m
Warranty	Xativa large format printing materials are guaranteed to meet Xativa published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly	

