



A premium quality instant dry satin photo paper with a special micro-porous coating provides excellent ink absorption, large colour gamut and improved black definition.

Ideal for high quality photographic prints, posters, visual mock ups and client proofs.

Specially developed for the booming photography and graphic design market this satin finish paper enables you to create photo-realistic prints of impressive colour quality and detail. Thanks to the special ink absorption layer high amounts of ink dries immediately and the print is water resistant.

The special properties of this paper also enable you to achieve a large colour gamut and rich black density.

All specifications are correct at time of print and are subject to change without notice. E&OE

Product specifications

|                             |                                                                                                                                                                                                         |              |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| Weight                      | 260 g/m <sup>2</sup> (+/- 10gsm) DIN EN ISO536                                                                                                                                                          |              |
| Thickness                   | 265 microns (+/- 12 microns) ISO534                                                                                                                                                                     |              |
| Opacity                     | > 96% (+/-4%) DIN53146                                                                                                                                                                                  |              |
| Whiteness                   | 96 (+/- 3%) ISO2471                                                                                                                                                                                     |              |
| Finish                      | Satin Matt                                                                                                                                                                                              |              |
| Gloss value 60°             | 47% (+/- 5)                                                                                                                                                                                             |              |
| Smoothness                  | > 750                                                                                                                                                                                                   |              |
| Stiffness md                | 63 (+/- 0.8mN) ISO2493                                                                                                                                                                                  |              |
| Stiffness cd                | 39 (+/- 0.5mN) ISO2493                                                                                                                                                                                  |              |
| Operating temperature       | 15 to 100 degrees centigrade                                                                                                                                                                            |              |
| Operating humidity          | 20 to 80% RH                                                                                                                                                                                            |              |
| Dry time                    | Instant dry with heating (at 23 degrees centigrade, 50% RH)                                                                                                                                             |              |
| Shelf time                  | 2 years, unopened in original packaging                                                                                                                                                                 |              |
| Storage temperature         | 0 to 40 degrees centigrade                                                                                                                                                                              |              |
| Storage humidity            | 5 to 95% RH                                                                                                                                                                                             |              |
| Country of origin           | Product of Germany                                                                                                                                                                                      |              |
| Printer / Ink Compatibility | Compatible with all aqueous based dye, pigment and UltraChrome K3 Inks from all leading manufacturers such as Canon, Epson and Hewlett Packard                                                          |              |
| Lamination                  | Can be laminated with commercially available thermal and pressure sensitive films                                                                                                                       |              |
| Ordering information        | Product numbers                                                                                                                                                                                         | Roll Sizes   |
|                             | XPSPRO260-17                                                                                                                                                                                            | 432mm x 30m  |
|                             | XPSPRO260-24                                                                                                                                                                                            | 610mm x 30m  |
|                             | XPSPRO260-36                                                                                                                                                                                            | 914mm x 30m  |
|                             | XPSPRO260-42                                                                                                                                                                                            | 1067mm x 30m |
| Warranty                    | Xativa large format printing materials are guaranteed to meet Xativa published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly |              |

